



Product Code	ITP-CHR-505231
Description	i-Tap Basin Mixer, Wall Mounted • CPU, • Touchpad, • Power Supply System with CPU Cable, • Touchpad Cable - 1meters, • Braided Hoses 18" - 03 Nos, • NRV Set in-Built - 02 Nos, • Filter - 02 Nos, • Touchpad mounting box, • Metallic clamp & screw
Water Supply	Hot & Cold (2 inlets)
Water Temperature	5 °C - 65 °C
Inlet Water Connection	1/2" BSP (15mm)
Water Pressure	1.5 Bar - 5.0 Bar (Dynamic)
Recommended Water Pressure	3.0 Bar (Dynamic)
Flow Rate	ADJUSTABLE FLOW Maximum-13.0 LPM Minimum-2.0 LPM @ 3 Bar with regular Aerator
Auto shut-off	10 Minutes
Material Composition Specification in Percentage	Brass Ingots as per IS:1264-1997 Cu (58.0-63.0), Sn (0.0-1.0), Pb (0.5-2.5), Ni (0.0-1.0), Al (0.2-0.8), Mn (0.0-0.5), Total Impurity (0.0-2.0), Zn (Remainder) Brass Rod as per IS:319-1989 Cu (56.0-59.0), Pb (2.0-3.5), Fe (0.0-0.35), Total Impurity (0.0-0.7), Zn (Remainder) Brass Sheets as per IS:410-1977 Cu (61.5-64.5), Pb (0.0-0.3), Fe (0.0-0.075), Total Impurity (0.0-0.6), Zn (Remainder)
IP Rating	IP53
i-Tap Touchpad	IP65
Water Tightness	10 bar (Pass)
Pressure Resistance	15 bar (Pass)
Aerator Size	WRAS, ACS Approved (M24X1)
Finish	Plating: Nickel-13.0 micron Chromium-0.40 micron Salt Spray (700 hrs + Validated) Adhesion (Pass)
Available Colour Finishing	Antique Bronze (ABR), Antique Copper (ACR), Black Chrome (BCH), Black Matt (BLM), Graphite (GRF) & Stainless Steel Finish (SSF)
DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. 10% variation in flow rate may be possible. Jaquar reserves the right to make the necessary amendments at any time without prior notice.	