



	NAV CUD E1E04EDD
Product Code	NAV-CHR-515845BR
	False ceiling installation kit for Navia Rainjoy Shower 450mm consisting of 1 Bracket, 4 Anchors, 4 Stud bolts, 12 Hex nuts (Compatible with NAV-515845SH & NAV-515847SH)
Product Code	NAV-CHR-515847SH
	Navia RAINJOY Shower 450mm AISI 304 stainless steel with RGB LED lights & remote control, without
	installation kit for false ceiling
	• Chromo therapy (RGB): LED x 0.23W with 12V Power Supply (SMPS) including Controller, connecting to AC 10
	240V, 50-60Hz • 3-functions
Flow Rate	• Rain, • Intense, • Laminar (Not Final)
	Rain - 44.08 LPM @ 3 bar Intense - 24.15 LPM @ 3 bar
	Laminar - 46.88 LPM @ 3 bar
Recommended Water Pressure	
	1.0 Bar - 3.0 Bar
Mount Type	Ceiling Mounting
Spray Modes	Rain, Intense & Laminar Functions
	STAINLESS STEEL: Nickel 8.0-11.0, Chromium 18.0-20.0, Manganese 0.0 - 2.0, Carbon 0.0-0.08, Iron Remainder
Material Composition	(AISI 304)
Specification in Percentage	
Specification in Fercentage	ABS: Specific Gravity (g/cm²) 1.06-1.10, Melt Mass Flow Rate (g/10 min.) 20-26, Rockwell Hardness 95-115,
	DTUL @ 66 psi (0.45 MPa) (0C) 78-102
REMOTE CONTROL	
	ON/OFF •
	Speed Down Push - button to speed
	Push - button to speed down penoramic mode  Speed Up  Rush + button to speed down penoramic mode
	Mono color - next   Increase Brightness of LED
	Mono color - previous  Decrease Brightness of LED
	Automatic mode changing previous
	Artize
	Reference
	Nuch Puch
	HOW TO CHANGE BATTERY
	OLIDOMO TUEDADV (DOD)
LED POWER SUPPLY	CHROMO THERAPY (RGB)      LED x 0.23W with 12V Power Supply (SMPS) including Controller, connecting to
	AC 100-240V, 50-60Hz
	• COLOR VARIATION •
	Mono Color (RGB) Chromo Theraphy
	more dots (real)
	LED On / Off
	Switch Sensor by Remote Control
	*
Finish	Salt Spray (500 hrs + Validated)
Available Finishing	Adhesion (Pass)  Black Matt (BLM), Blush Gold Bright PVD (BGP), Black Bright PVD (BBP) & Gold Bright PVD (GBP)

DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. 10% variation in flow rate may be possible. Jaquar reserves the right to make the necessary amendments at any time without prior notice.