## www.artize.com

## Ärtize



| Product Code (Only CHR Finish)  | OSA-CHR-70005BR<br>False ceiling installation kit for RaiNJOY Shower 600X472mm consisting of 1 Bracket, 4 Anchors, 4 Stud bolts, 12 Hex<br>nuts (Compatible with OSA-70005SH, OSA-70007SH & OSA-70009SH)  |
|---|---|
| Product Code (Only CHR Finish)  | OSA-CHR-70005SHiV6<br>RaiNJOY Shower 600X472mm AISI 304 stainless steel with RGB LED lights remote control & without installation kit<br>for false ceiling<br>• Chromo therapy (RGB): LED x 0.23W with 12V Power Supply (SMPS) Including Controller, connecting to AC 100-<br>240V, 50-60Hz<br>• 3-functions<br>• Rain, • Intense, • 4 X Mist (Compatible with iV6)   |
| Product Code (For Color Finish)   | OSA-XXX-70005iV6<br>RaiNJOY Shower 600X472mm AISI 304 stainless steel with RGB LED lights remote control & with installation kit for<br>false ceiling<br>• Chromo therapy (RGB): LED x 0.23W with 12V Power Supply (SMPS) Including Controller, connecting to AC 100-<br>240V, 50-60Hz<br>• 3-functions<br>• Rain, • Intense, • 4 X Mist (Compatible with iV6)  |
| Flow Rate   | Rain - 55.00 LPM @ 3 bar<br>Intense - 45.20 LPM @ 3 bar<br>Mist - 8.00 LPM @ 3 bar  |
| Recommended Water Pressure  | 1.0 Bar - 3.0 Bar   |
| Mount Type  | Ceiling Mounting  |
| Spray Modes   | Rain, Intense & Mist Functions  |
| Material Composition<br>Specification in Percentage   | STAINLESS STEEL: Nickel 8.0-11.0, Chromium 18.0-20.0, Manganese 0.0 - 2.0, Carbon 0.0-0.08, Iron Remainder (AISI 304)       ABS: Specific Gravity (g/cm <sup>2</sup> ) 1.06-1.10, Melt Mass Flow Rate (g/10 min.) 20-26, Rockwell Hardness 95-115, DTUL @ 66 psi (0.45 MPa) (0C) 78-102   |
| REMOTE CONTROL  | Automatic mode changing - next<br>Streed Down<br>Automatic mode changing - next<br>Provide Mode ON<br>Served Up<br>Net - table to grad down proverse mode<br>Mono color - next<br>Mono color - previous<br>Automatic mode changing previous |
| LED POWER SUPPLY  | CHROMO THERAPY (RGB)  LED x 0.23W with 12V Power Supply (SMPS) including Controller, connecting to<br>AC 100-24W, 50-60%; COLOR VARIATION  Mono Color (RGB) Chromo Theraphy LED On / Off Swlitch Sensor by Remote Control   |
| Finish  | Salt Spray (500 hrs + Validated)<br>Adhesion (Pass)   |
| Available Finishing   | Antique Bronze (ABR), Antique Copper (ACR), Black Chrome (BCH), Blush Gold Bright PVD (BGP), Black Matt (BLM),<br>Gold Bright PVD (GBP), Gold Matt PVD (GMP), Graphite (GRF) & Stainless Steel (SSF)  |
| DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. 10% variation in flow rate may be possible. Jaquar reserves the right to make the necessary amendments at any time without prior notice. |   |