



<b>Product Code</b>	OSA-CHR-70021
<b>Description</b>	<p>Rainjoy+ Shower 500X500mm AISI 304 stainless steel with RGB LED lights remote control &amp; <b>with installation kit for false ceiling</b></p> <ul style="list-style-type: none"> <li>Chromo therapy (RGB): LED x 0.23W with 12V Power Supply (SMPS) Including Controller, connecting to AC 100-240V, 50-60Hz</li> <li>4-functions <ul style="list-style-type: none"> <li>Rain, Intense, Bold Massage, 4 X Mist</li> </ul> </li> </ul>
<b>Flow Rate</b>	<p>Rain - 51.13 LPM @ 3 bar  Intense - 25.62 LPM @ 3 bar  Bold Massage - 17.68 LPM @ 3 bar  Mist - 5.30 LPM @ 3 bar</p>
<b>Recommended Water Pressure</b>	1.0 Bar - 3.0 Bar
<b>Mount Type</b>	Ceiling Mounting
<b>Spray Modes</b>	Rain, Intense, Bold Massage & Mist Functions
<b>Material Composition Specification in Percentage</b>	<p><b>STAINLESS STEEL:</b> Nickel 8.0-11.0, Chromium 18.0-20.0, Manganese 0.0 - 2.0, Carbon 0.0-0.08, Iron Remainder (AISI 304)</p> <p><b>ABS:</b> Specific Gravity (g/cm<sup>2</sup>) 1.06-1.10, Melt Mass Flow Rate (g/10 min.) 20-26, Rockwell Hardness 95-115, DTUL @ 66 psi (0.45 MPa) (OC) 78-102</p>
<b>REMOTE CONTROL</b>	<p>HOW TO CHANGE BATTERY</p>
<b>LED POWER SUPPLY</b>	<ul style="list-style-type: none"> <li><b>CHROMO THERAPY (RGB)</b> • LED x 0.23W with 12V Power Supply (SMPS) including Controller, connecting to AC 100-240V, 50-60Hz</li> <li><b>COLOR VARIATION</b> •</li> </ul> <div style="display: flex; justify-content: space-around; align-items: center;"> <div style="text-align: center;"> <p>Mono Color (RGB)</p> </div> <div style="text-align: center;"> <p>Chromo Therapy</p> <p>LED On / Off Switch Sensor by Remote Control</p> </div> </div>
<b>Finish</b>	Salt Spray (500 hrs + Validated) Adhesion (Pass)
<b>Available Finishing</b>	Antique Bronze (ABR), Antique Copper (ACR), Black Chrome (BCH), Blush Gold Bright PVD (BGP), Black Matt (BLM), Gold Bright PVD (GBP), Gold Matt PVD (GMP), Graphite (GRF) & Stainless Steel (SSF)
<p>DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. 10% variation in flow rate may be possible. Jaquar reserves the right to make the necessary amendments at any time without prior notice.</p>	