
Ärtıze





Hex nuts (Compatible with OSA-70005SH; OSA-70007SH & OSA-70005SH) OSA-CHR.70009SH (SMU01'Shower 600X472mm AISI 304 stainless steel with RGB LED lights remote control & without installation in for false celling. Product Code (Only CHR Finish) Chromo therapy (RGB): LED x 0.23W with 12V Power Supply (SMPS) Including Controller, connecting to AC 10 240%; 50-60Hz Product Code (For Color Finish) Chromo therapy (RGB): LED x 0.23W with 12V Power Supply (SMPS) Including Controller, connecting to AC 10 240%; 50-60Hz Product Code (For Color Finish) Chromo therapy (RGB): LED x 0.23W with 12V Power Supply (SMPS) Including Controller, connecting to AC 10 240%; 50-60Hz Product Code (For Color Finish) Chromo therapy (RGB): LED x 0.23W with 12V Power Supply (SMPS) Including Controller, connecting to AC 10 240%; 50-60Hz Product Code (For Color Finish) Chromo therapy (RGB): LED x 0.23W with 12V Power Supply (SMPS) Including Controller, connecting to AC 10 240%; 50-60Hz Flow Rate Rain - 55:00 LPM (# 3 bar (Intense: 43:01 LPM (# 3 bar) Recommended Water Presure (Intense: 40 Waterfall Functions Specification in Percentage Rain, Intense: 8 Waterfall Functions Specification in Percentage REMOTE CONTROL Specific Gravity (g/cm ¹) 1.06-1.10, Melt Mass Flow Rate (g/10 min.) 20-26, Rockwell Hardness 95-115, DT		OSA-CHR-70005BR
OSA-CHR 700095H Product Code (Only CHR Finish) Product Code (Only CHR Finish) - Chromo Therapy (RGB): LED x 0.23W with 12V Power Supply (SMP5) Including Controller, connecting to AC 10 240, 50-60Hz - Sharin Interace, 2 X Waterfall OSA-X0X.70009 Rail/UVD Shower 600X/72mm AISI 304 stainless steel with RGB LED lights remote control & with installation kit for false celling Product Code (For Color Finish) Product Code (For Color Finish) Product Code (For Color Finish) - Chromo therapy (RGB): LED x 0.23W with 12V Power Supply (SMP5) Including Controller, connecting to AC 10 240, 50-60Hz - Sharin Intense, 2 X Waterfall Recommended Water Pressure Intense - 46.20 LPM @ 3 bar Meterial Composition Specification in Percentage Reference Control & Waterfall Functions STANIXESS STEEL: Nickel 8.0-11.0, Chromium 18.0-20.0, Manganese 0.0 - 2.0, Carbon 0.0-0.08, Iron Remainder (AISI 304) Material Composition Specification in Percentage REMOTE CONTROL LED POWER SUPPLY - Celling Mounting Sait Spray (500 hrs + Validated) Adhesion (pass) - Control Col View (200 hrs + Validated) Adhesion (Pass) - Col View (200 hrs + Validated) Adhesion (Pass) - Col View (200 hrs + Validated) Adhesion (Pass) - Col Vi	Product Code (Only CHR Finish)	False ceiling installation kit for RaiNJOY Shower 600X472mm consisting of 1 Bracket, 4 Anchors, 4 Stud bolts, 12
OSA-CHR 700095H Product Code (Only CHR Finish) Product Code (Only CHR Finish) - Chromo therapy (KBB): LED x 0.23W with 12V Power Supply (SMPS) Including Controller, connecting to AC 10 240, 50-60Hz - Shar, Interines, 2 X Waterfall OSA-WAR 70009 Rail/OV Shower 600X172mm AISI 304 stainless steel with RGB LED lights remote control & with installation kit for false celling Product Code (For Color Finish) Product Code (For Color Finish) - Chromo therapy (RBB): LED x 0.23W with 12V Power Supply (SMPS) Including Controller, connecting to AC 10 240, 50-60Hz - Shar Intense, 2 X Waterfall Recommended Water Pressure - Celling Mounting Status: Status Waterfall - 23.01 LPM @ 3 bar Mount Type Celling Mounting Status: Status: Status Status: Status: Status Status: Status: Status: Status Status: Status: Status: Status Bas: Specific Gravity (g/cm ³) 1.06-1.10, Melt Mass Flow Rate (g/10 min.) 20-26, Rockwell Hardness 95-115, DTL @ 6 6 pt (0.45 MPa) (0C) 78-102 IED POWER SUPPLY LED POWER SUPPLY Finish Asit Spray (500 hrs + Validated) Adhesion (pass) Adhesion (Pass)		Hex nuts (Compatible with OSA-70005SH, OSA-70007SH & OSA-70009SH)
Product Code (Only CHR Finish) kit for false ceiling Product Code (Only CHR Finish) - Chrome therapy (R6B): LED x 0.23W with 12V Power Supply (SMPS) including Controller, connecting to AC 10 240V, 50 66Hz Product Code (For Color Finish) - Salon, Intense, 2 X Waterfall Real, Intense, 2 X Waterfall CoA-XXXX-70009 Raino, Intense, 2 X Waterfall - Chrome therapy (R6B): LED x 0.23W with 12V Power Supply (SMPS) including Controller, connecting to AC 10 240V, 50-60Hz - Volume therapy (R6B): LED x 0.23W with 12V Power Supply (SMPS) including Controller, connecting to AC 10 240V, 50-60Hz - Salon, Intense, 2 X Waterfall Rino: So 20 Waterfall Rino: Intense, & Waterfall Recommended Water Pressure Ceiling Mounting Status (Go G Gravity (g)(m ³) Status (Go G Gravity (g)(m ³) <td></td> <td></td>		
Product Code (Only CHR Finish) Ikit for false ceiling Product Code (Only CHR Finish) Onrome therapy (RGB): LED x 0.23W with 12V Power Supply (SMPS) including Controller, connecting to AC 10 240V, 50-60Hz Salin, Intense, 2 X Waterfall Product Code (For Color Finish) Onrome therapy (RGB): LED x 0.23W with 12V Power Supply (SMPS) including Controller, connecting to AC 10 240V, 50-60Hz Afunctions Salin, Intense, 2 X Waterfall Product Code (For Color Finish) Onrome therapy (RGB): LED x 0.23W with 12V Power Supply (SMPS) including Controller, connecting to AC 10 240V, 50-60Hz Afunctions Salin, Intense, 2 X Waterfall Rain, Intense, 46.30 LPM @ 3 bar Mount Type Ceiling Mounting Stal VPM @ 3 bar Material Composition Specific Gravity (g/cm³) 1.06-1.10, Melt Mass Flow Rate (g/10 min.) 20-26, Rockwell Hardness 95-115, DTL @ 66 pai (0.45 MPa) (0C) 78-102 Ceined Date (GGB) Ceined Date (GGB) Ceined Date (GGB) Ceined Code (GGB)	Product Code (Only CHR Finish)	RaiNJOY Shower 600X472mm AISI 304 stainless steel with RGB LED lights remote control & without installation
2400, 56 oft-it • A functions • A functions • Rain,* Intense,* 2 X Waterfall OSA-XXX-70009 Product Code (For Color Finish) • Chromo therapy (FGB): LED x 0.23W with 12V Power Supply (SMPS) Including Controller, connecting to AC 10 240V, 50 ofbit. 240V, 50 ofbit. • Aninot Sing DPM @ 3 bar Product Code (For Color Finish) • Rain, intense, 2 X Waterfall Rain - S50 DPM @ 3 bar Waterfall - 42.30 DPM @ 3 bar Mount Type Spray Modes Rain, Intense, 2 X Waterfall Functions • Rain, Intense, 4 63.0 DPM @ 3 bar Material Composition Specification in Percentage AS: Specific Gravity (g/cm ²) 1.06-1.10, Melt Mass Flow Rate (g/10 min.) 20-26, Rockwell Hardness 95-115, DTL @ 66 pi (0.45 MPa) (0C) 78-102 REMOTE CONTROL LED POWER SUPPLY • CHRONO THERAPY (RDB). LED POWER SUPPLY • CHRONO THERAPY (RDB). LED POWER SUPPLY • CHRONO THERAPY (RDB). LED POWER SUPPLY		
• 3-functions • Alan, Fintense, * 2.X Waterfall OSA-XXX-7009 RAINUY Shower 600X422mm AISI 304 stainless steel with RGB LED lights remote control & with Installation Kill Product Code (For Color Finish) • Chrome therapy (RGB): LED x 0.23W with 12V Power Supply (SMPS) Including Controller, connecting to AC 10 2400, 50-60Hz • Rain, Intense, * 2.X Waterfall Recommended Water Pressure • Alan, Intense, * 2.X Waterfall Recommended Water Pressure • Cleaning Mounting Spray Modes Rain, Intense, * A.Waterfall Functions Spray Modes Rain, Intense, & Waterfall Functions Spray Modes Recommended Water Pressure Ass: Specific Gravity (g/cm ²) 1.06-1.10, Ohromium 18.0-20.0, Manganese 0.0-2.0, Carbon 0.0-0.08, Iron Remainder (AISI 304) Ass: Specific Gravity (g/cm ²) 1.06-1.10, Melt Mass Flow Rate (g/10 min.) 20-26, Rockwell Hardness 95-115, DTL 000 Functions More Coder, reader of the Base (g/10 min.) 20-26, Rockwell Hardness 95-115, DTL 000 Functions Functions Funce (G/10 Functions Functions (G/10 Funce (G/10 Funct		• Chromo therapy (RGB): LED x 0.23W with 12V Power Supply (SMPS) Including Controller, connecting to AC 100-
 A Bain, Intense, 2 X Waterfall OSA-XXX.7000 OSA-XXX.7000 OSA-XXX.7000 SalVOY Shower 5000/472mm AISI 304 stainless steel with RGB LED lights remote control & with installation kit for false calling For Gold Finshilt A Grant Consection - Salvox 7000 Provide 1000/472mm AISI 304 stainless steel with RGB LED lights remote control & with installation kit for false calling - Chromo therapy (RGB): LED x 0.23W with 12V Power Supply (SMPS) including Controller, connecting to AC 10 2409, 50-60Hz - Salvox 1000 - Salvox 10000 - Salvox 100000 - Salvox 100000 - Salvox 10000000000000 - Salvox 1000000000000000000000000000000000000		240V, 50-60Hz
Image: Control of Contrect of Contrect of Control of Control of Control of Control of C		• 3-functions
ReMOUX Shower 600X472mm AISI 304 stainless steel with RGB LED lights remote control & with installation kin for false ceiling for false ceiling stain - 556 of the reary (RGB): LED x 0.23W with 12V Power Supply (SMPS) including Controller, connecting to AC 10 2400, 596 obtiz - 3-functions - 8ain - 556 of UPM @ 3 bar Intense - 45, 30 LPM @ 3 bar Material - 42, 30 LPM @ 3 bar Ceiling Mounting Spray Modes Recommended Water Pressur Mount Type Ceiling Mounting Staff, LED x 0.23W with 13V. Power 3upply (SMPS) including Controller, connecting to AC 10 2400, 596 obtiz - 440, 10 Bar - 350 LPM @ 3 bar Intense - 45, 30 LPM @ 3 bar Recommended Water Pressur Mount Type Ceiling Mounting Staff, LED x 0.23W with 18, 0-20.0, Manganese 0.0 - 2.0, Carbon 0.0-0.08, Iron Remainder (AISI 304) Staff, Intense & Waterfall Functions Staff, Intense & Waterfall Functions Staff, Intense & Waterfall Functions Staff, Iron Berger, Ber		Rain, Intense, 2 X Waterfall
Product Code (For Color Finish) Increase Beginness - Chromo therapy (RGB): LED x 0.23W with 12V Power Supply (SMPS) Including Controller, connecting to AC 10 2400, 50-60Hz - Rain, Intense, 2 X Waterfall Rain, Intense, 4 2.30 LPM @ 3 bar Waterfall - 42.30 LPM @ 3 bar Waterfall - Colling Mounting Spray Modes Staffication in Percentage ABs: Specific Gravity (g/cm ²) 1.06-1.10, Melt Mass Flow Rate (g/10 min.) 20-26, Rockwell Hardness 95-115, DTL @ 66 psi (0.45 MPa) (0C) 78-102 REMOTE CONTROL REMOTE CONTROL LED POWER SUPPLY - CHROMO THERMAY (RGB) LED POWER SUPPLY Satt Spray (500 hrs + Validated) Adhesion (Pass) Available Finishing Available Finishing Available Finishing Available Finishing		OSA-XXX-70009
Product Code (For Color Finish) Chromo the apy (RGB): LED x 0.23W with 12V Power Supply (SMPS) including Controller, connecting to AC 10 240V, 50-60Hz S-Hunctions Rain - Sto Chromo the apy (RGB): LED x 0.23W with 12V Power Supply (SMPS) including Controller, connecting to AC 10 240V, 50-60Hz S-Hunctions Rain - Sto Chromo the apy (RGB): LED x 0.23W with 12V Power Supply (SMPS) including Controller, connecting to AC 10 240V, 50-60Hz Stany Intense, 2 & Waterfall Rain - Sto Chromo the apy (RGB) and response of the appendix of th	Product Code (For Color Finish)	RaiNJOY Shower 600X472mm AISI 304 stainless steel with RGB LED lights remote control & with installation kit
240V, 50-60Hz • 3-functions • Rain, Intense, 2.X.Waterfall Rein Fintense, 2.X.Waterfall Rain - Intense, 4.23.0 LPM @ 3 bar Waterfall - 42.30 LPM @ 3 bar Mount Type Celling Mounting Spray Modes Rain, Intense & Waterfall Functions Strait, Elss Stratus Spray Modes Rain, Intense & Waterfall Functions Strait, Elss Stratus Spray Modes Rain, Intense & Waterfall Functions Strait, Elss Stratus Spray Modes Rain, Intense & Waterfall Functions Strait, Elss Stratus Spray Modes Remote composition Specification in Percentage AB: Specific Gravity (g/cm ²) 1.06-1.10, Melt Mass Flow Rate (g/10 min.) 20-26, Rockwell Hardness 95-115, DTL @ 66 psi (0.45 MPa) (OC) 78-102 Image: Specific Gravity (g/cm ²) 1.06-1.10, Melt Mass Flow Rate (g/10 min.) 20-26, Rockwell Hardness of LED More color - provide functions taxed and and taxed and ta		for false ceiling
• 3-functions • Administrations • Rain, - Intense, - 2 X Waterfall • Rain, - Intense, - 2 X Waterfall Flow Rate Intense, - 46, 30 LPM @ 3 bar Recommended Water Pressure 1.0 Bar, - 3.0 Bar Mount Type Celling Mounting Spray Modes Rain, Intense, - 44, 30 LPM @ 3 bar Material Composition STAINLESS STEEL: Nickel 8.0-11.0, Chromium 18.0-20.0, Manganese 0.0 - 2.0, Carbon 0.0-0.08, Iron Remainder (AIS 304) Spray Modes STAINLESS STEEL: Nickel 8.0-11.0, Chromium 18.0-20.0, Manganese 0.0 - 2.0, Carbon 0.0-0.08, Iron Remainder (AIS 304) Specification in Percentage ABS: Specific Gravity (g/cm ²) 1.06-1.10, Melt Mass Flow Rate (g/10 min.) 20-26, Rockwell Hardness 95-115, DTL @ 66 psi (0.45 MPa) (0C) 78-102 REMOTE CONTROL Image: Comparison of LED Powers Enginees of LED Powers Supply (MMPB) Including Controller, Comparison of LED Powers Enginees of LED Powers Supply Comparison of LED Powers Supply (SMPB) Including Controller, Comparison of LED Powers Supply (SMPB) Including Contr		• Chromo therapy (RGB): LED x 0.23W with 12V Power Supply (SMPS) Including Controller, connecting to AC 100-
• Rain, Intense, • 2 X Waterfall Rain - 55.60 LPM @ 3 bar Recommended Water Pressure 1.0 Bar - 30.0 EM @ 3 bar Waterfall - 42.30 LPM @ 3 bar Material Composition Specification in Percentage ABS: Specific Gravity (g/cm ²) 1.06-1.10, Melt Mass Flow Rate (g/10 min.) 20-26, Rockwell Hardness 95-115, DTL @ 66 psi (0.45 MPa) (0C) 78-102 REMOTE CONTROL LED POWER SUPPLY Salt Sp		240V, 50-60Hz
Flow Rate Rain - 55.60 LPM @ 3 bar Intense - 46.30 LPM @ 3 bar Recommended Water Pressure Mount Type 10 Bar - 3.0 Bar Ceiling Mounting Spray Modes Rain, Intense & Waterfall Functions Status STAINLESS STEEL: Nickel 8.0-11.0, Chromium 18.0-20.0, Manganese 0.0 - 2.0, Carbon 0.0-0.08, Iron Remainder (AISI 304) Material Composition Specification in Percentage Status Street: Nickel 8.0-11.0, Melt Mass Flow Rate (g/10 min.) 20-26, Rockwell Hardness 95-115, DTC @ 66 psi (0.45 MPa) (0C) 78-102 REMOTE CONTROL Oncore - next More order - provide - CHROMO THERAPY (pd) + LED POWER SUPPLY Automatic mode charging - nay - CHROMO THERAPY (pd) + LED POWER SUPPLY LED POWER SUPPLY Salt Spray (500 hrs + Validated) Adhesion (Pass) Andiesion (Pass) Concore (RGB) Concore (RGB) Andiesion (Pass) Concore (RGB) Chromo Therapy (BMFB) including Controles, connecting to Actionatic mode charging provide - LED On / OF Suite Bianear by Remote Control Finish Salt Spray (500 hrs + Validated) Adhesion (Pass) Concore (RGB) Chromo Therapy (BMFB) including Controles, connecting to Actionatic mode charging provide - CALCH VARIATION + Mono Color (RGB) Chromo Therapy (BMFB) including Controles, connecting to Actionatic mode charging provide - CALCH VARIATION + LED POWER SUPPLY Salt Spray (500 hrs + Validated) Adhesion (Pass) Chromo Therapy (BMFB) including Controles, connecting to Actionatic and to ensure factual accuracy, the information presented subject to changes due to requirements in		• 3-functions
Flow Rate Intense - 46.30 LPM @ 3 bar Recommended Water Pressure 1.0 Bar - 3.0 Bar Mount Type Celling Mounting Spray Modes Rain, Intense & Waterfall Functions Strait NESS STELE: Nickel 8.0-11.0, Chromium 18.0-20.0, Manganese 0.0 - 2.0, Carbon 0.0-0.08, Iron Remainder (AISI 304) Material Composition Strait NESS STELE: Nickel 8.0-11.0, Chromium 18.0-20.0, Manganese 0.0 - 2.0, Carbon 0.0-0.08, Iron Remainder (AISI 304) ABS: Specific Gravity (g/cm ²) 1.06-1.10, Melt Mass Flow Rate (g/10 min.) 20-26, Rockwell Hardness 95-115, DTL @ 66 psi (0.45 MPa) (0C) 78-102 REMOTE CONTROL Image: Specific Gravity (g/cm ²) 1.06-1.10, Melt Mass Flow Rate (g/10 min.) 20-26, Rockwell Hardness 95-115, DTL @ 66 psi (0.45 MPa) (0C) 78-102 LED POWER SUPPLY Image: Specific Gravity (g/cm ²) 1.06-1.10, Melt Mass Flow Rate (g/10 min.) 20-26, Rockwell Hardness effective and the specific data of the		Rain, Intense, 2 X Waterfall
Waterfail: 42.30 LPM @ 3 bar Recommended Water Pressure L0 Bar : 3.0 Bar Mount Type Celling Mounting Spray Modes Rain, Intense & Waterfail Functions Strain Composition Specific Gravity (g/cm²) 1.06-1.10, Chromium 18.0-20.0, Manganese 0.0 - 2.0, Carbon 0.0-0.08, Iron Remainder (AISI 304) Specification in Percentage Sit Specific Gravity (g/cm²) 1.06-1.10, Melt Mass Flow Rate (g/10 min.) 20-26, Rockwell Hardness 95-115, DTL @ 66 psi (0.45 MPa) (0C) 78-102 REMOTE CONTROL ON/OFF Instructure Control ON/OFF Instructure Control Image: Control Con		Rain - 55.60 LPM @ 3 bar
Recommended Water Pressure 1.0 Bar - 3.0 Bar Mount Type Celling Mounting Spray Modes Rain, Intense & Waterfall Functions Statistics STEEL: Nickel 8.0-11.0, Chromium 18.0-20.0, Manganese 0.0 - 2.0, Carbon 0.0-0.08, Iron Remainder (AISI 304) Specification in Percentage ABS: Specific Gravity (g/cm ²) 1.06-1.10, Melt Mass Flow Rate (g/10 min.) 20-26, Rockwell Hardness 95-115, DTL @ 66 psi (0.45 MPa) (0C) 78-102 REMOTE CONTROL ON/OFF REMOTE CONTROL ON/OFF LED POWER SUPPLY - CHEMON THEMPTY (FIGB) - Including Controller, connecting to Addromatic mode charging the second of LED on 2007 views equal to the second of LED on 2007 views equal to the second of LED on 2007 views equal to the second of LED on 2007 views equal to the second of LED on 2007 views equal to the second of LED on 2007 views equal to the second of LED on 2007 views equal to the second of LED on 2007 views equal to the second of LED on 2007 views equal to the second of LED on 2007 views equal to the second of LED on 2007 views equal to the second of LED on 2007 views equal to the second of LED on 2007 views equal to the second of LED on 2007 views equal to the second of LED on 2007 views equal to the second of LED on 2007 views equal to the second equal to the second of LED on 2007 views equal to the second of LED on 2007 views equal to the second equal to the second of LED on 2007 views equal to the second of LED on 2007 views equal to the second equal to the second of LED on 2007 views equal to the second equal to the second to the second equal to the second equale	Flow Rate	Intense - 46.30 LPM @ 3 bar
Mount Type Ceiling Mounting Spray Modes Rain, Intense & Waterfall Functions STAINUESS STEEL: Nickel 8.0-11.0, Chromium 18.0-20.0, Manganese 0.0 - 2.0, Carbon 0.0-0.08, Iron Remainder (AISI 304) Material Composition Specification in Percentage ABS: Specific Gravity (g/cm ²) 1.06-1.10, Melt Mass Flow Rate (g/10 min.) 20-26, Rockwell Hardness 95-115, DTL @ 66 psi (0.45 MPa) (0C) 78-102 REMOTE CONTROL REMOTE CONTROL LED POWER SUPPLY • OHROMO THERAPY (RGB) + LED to 0.240 VIII 124 Power Supply (SMPS) including Controller, connecting to Automatic mode of enging previous of 0.2007, 0000 Controller, connecting to Automatic mode of enging previous of 0.2007, 0000 Controller, connecting to Automatic mode of enging previous of 0.2007, 0000 Controller, connecting to Automatic mode of enging previous of 0.2007, 0000 Controller, connecting to Automatic mode of enging previous of 0.2007, 0000 Controller, connecting to Automatic mode of enging previous of 0.2007, 0000 Controller, connecting to Automatic mode of enging previous of 0.2007, 0000 Controller, connecting to Automatic mode of enging previous of 0.2007, 0000 Controller, connecting to Automatic mode of enging previous of 0.2007, 0000 Controller, connecting to Automatic mode of enging previous of 0.2007, 0000 Controller, connecting to Automatic mode of enging previous of 0.2007, 0000 Controller, connecting to Automatic mode of enging previous of 0.2007, 0000 Controller, connecting to Automatic mode of enging previous of 0.2007, 0000 Controller, connecting to Automatic mode of enging previous of 0.2007, 0000 Controller, connecting to Automatic mode of enging previous of 0.2007, 0000 Controller, connecting to Au		
Spray Modes Rain, Intense & Waterfall Functions Material Composition STAINLESS STELL: Nickel 8.0-11.0, Chromium 18.0-20.0, Manganese 0.0 - 2.0, Carbon 0.0-0.08, Iron Remainder (AISI 304) ABS: Specific Gravity (g/cm ²) 1.06-1.10, Melt Mass Flow Rate (g/10 min.) 20-26, Rockwell Hardness 95-115, DTL @ 66 psi (0.45 MPa) (0C) 78-102 REMOTE CONTROL	Recommended Water Pressure	
STAINLESS STEEL: Nickel 8.0-11.0, Chromium 18.0-20.0, Manganese 0.0 - 2.0, Carbon 0.0-0.08, Iron Remainder (AISI 304) Specification in Percentage ABS: Specific Gravity (g/cm ²) 1.06-1.10, Melt Mass Flow Rate (g/10 min.) 20-26, Rockwell Hardness 95-115, DTL @ 66 psi (0.45 MPa) (0C) 78-102 REMOTE CONTROL Image: Control of		
Material Composition (AISI 304) Specification in Percentage ABS: Specific Gravity (g/cm ²) 1.06-1.10, Melt Mass Flow Rate (g/10 min.) 20-26, Rockwell Hardness 95-115, DTL @ 66 psi (0.45 MPa) (0C) 78-102 REMOTE CONTROL	Spray Modes	Rain, Intense & Waterfall Functions
Material Composition Specification in Percentage ABS: Specific Gravity (g/cm ²) 1.06-1.10, Melt Mass Flow Rate (g/10 min.) 20-26, Rockwell Hardness 95-115, DTL @ 66 psi (0.45 MPa) (0C) 78-102 REMOTE CONTROL REMOTE CONTROL LED POWER SUPPLY Salt Spray (500 hrs + Validated) Adhesion (Pass) Antique Bronze (ABR), Antique Copper (ACR), Black Chrome (BCH), Blush Gold Bright PVD (BGP), Black Matt (BLM), Gold Bright PVD (GBP), Gold Matt PVD (GMP), Graphite (GRF) & Stanless Steel (SSF) DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in		
Specification in Percentage ABS: Specific Gravity (g/cm ²) 1.06-1.10, Melt Mass Flow Rate (g/10 min.) 20-26, Rockwell Hardness 95-115, DTU (Ø 66 psi (0.45 MPa) (OC) 78-102 REMOTE CONTROL Image: Control of the specific Gravity (g/cm ²) 1.06-1.10, Melt Mass Flow Rate (g/10 min.) 20-26, Rockwell Hardness 95-115, DTU (Ø 66 psi (0.45 MPa) (OC) 78-102 LED POWER SUPPLY Image: Control of the specific Gravity (g/cm ²) 1.06-1.10, Melt Mass Flow Rate (g/10 min.) 20-26, Rockwell Hardness 95-115, DTU (Ø 66 psi (0.45 MPa) (OC) 78-102 LED POWER SUPPLY Image: Control of the specific Gravity (g/cm ²) 1.06-1.10, Melt Mass Flow Rate (g/10 min.) 20-26, Rockwell Hardness 95-115, DTU (Ø 66 psi (0.45 MPa) (OC) 78-102 Finish Salt Spray (500 hrs + Validated) Adhesion (Pass) Control of the specific Gravity (g/cm ²) 1.06-1.10, Melt Mass Flow Ref. Available Finishing Salt Spray (500 hrs + Validated) Adhesion (Pass) Antique Copper (ACR), Black Chrome (BCH), Blush Gold Bright PVD (BGP), Black Matt (BLM), Gold Bright PVD (GBP), Gold Matt PVD (GMP), Graphite (GRF) & Stanless Steel (SF) DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in	Material Composition	(AISI 304)
ABS: Specific Gravity (g/cm ⁻) 1.06-1.10, Melt Mass Flow Rate (g/10 min.) 20-26, Rockwell Hardness 95-115, DT. @ 66 psi (0.45 MPa) (0C) 78-102 REMOTE CONTROL REMOTE CONTROL . CHROMO THERAPY (RGB) - LED 0.020W with 120 Provide Supply (SMPB) including Controller, connecting to Actionate the species of th		
REMOTE CONTROL CHROMO THERAPY (ROB) - Instruments on the changing previous of the control of th	opeentation in referrage	ABS: Specific Gravity (g/cm ²) 1.06-1.10, Melt Mass Flow Rate (g/10 min.) 20-26, Rockwell Hardness 95-115, DTUL
REMOTE CONTROL Speed Down - model managed - managed up - Speed U		@ 66 psi (0.45 MPa) (0C) 78-102
LED x 0.23W with 12V Power Supply (SMPS) including Controller, connecting to AC 100-240V, 50-60Hz • COLOR VARIATION • Mone Color (RGB)	REMOTE CONTROL	Speed Down Puth - button to speed down paroramic Mode ON Speed Up Puth + button to speed down paroramic mode Mono color - next Mono color - previous Artize Automatic mode changing - next Speed Up Puth + button to speed down paroramic mode Increase Brightness of LED Decrease Brightness of LED Automatic mode changing previous Artize
Finish Salt Spray (500 hrs + Validated) Adhesion (Pass) Available Finishing Antique Bronze (ABR), Antique Copper (ACR), Black Chrome (BCH), Blush Gold Bright PVD (BGP), Black Matt (BLM), Gold Bright PVD (GBP), Gold Matt PVD (GMP), Graphite (GRF) & Stainless Steel (SSF) DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in		LED x 0.23W with 12V Power Supply (SMPS) including Controller, connecting to AC 100-240V, 50-60Hz • COLOR VARIATION •
Finish Salt Spray (500 hrs + Validated) Adhesion (Pass) Available Finishing Antique Bronze (ABR), Antique Copper (ACR), Black Chrome (BCH), Blush Gold Bright PVD (BGP), Black Matt (BLM), Gold Bright PVD (GBP), Gold Matt PVD (GMP), Graphite (GRF) & Stainless Steel (SSF) DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in	LED POWER SUPPLY	
Finish Adhesion (Pass) Available Finishing Antique Bronze (ABR), Antique Copper (ACR), Black Chrome (BCH), Blush Gold Bright PVD (BGP), Black Matt (BLM), Gold Bright PVD (GBP), Gold Matt PVD (GMP), Graphite (GRF) & Stainless Steel (SSF) DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in		
Available Finishing Antique Bronze (ABR), Antique Copper (ACR), Black Chrome (BCH), Blush Gold Bright PVD (BGP), Black Matt (BLM), Gold Bright PVD (GBP), Gold Matt PVD (GMP), Graphite (GRF) & Stainless Steel (SSF) DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in	Finish	
Available Finishing (BLM), Gold Bright PVD (GBP), Gold Matt PVD (GMP), Graphite (GRF) & Stainless Steel (SSF) DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in		
DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in	Available Finishing	
	DISCLAIMER: Our every effort has	
different sites, markets and/ or countries. 10% variation in flow rate may be possible. Jaquar reserves the right to make the necessary amendmen	•	
at any time without prior notice.		