




Product Code (Only STL Finish)	OSA-STL-70011BR False ceiling installation kit for RaiNJOY Shower 1000X750mm consisting of 1 Bracket, 4 Anchors, 4 Stud bolts, 12 Hex nuts (Compatible with OSA-70011SH & OSA-70015SH)
Product Code (Only STL Finish)	OSA-STL-70011SH RaiNJOY Shower 1000X750mm AISI 304 stainless steel with RGB LED lights remote control & without installation kit for false ceiling <ul style="list-style-type: none"> Chromo therapy (RGB): LED x 0.23W with 12V Power Supply (SMPS) Including Controller, connecting to AC 100-240V, 50-60Hz 4-functions <ul style="list-style-type: none"> Rain, Intense, Waterfall, Water Column
Product Code (For Color Finish)	OSA-XXX-70011 RaiNJOY Shower 1000X750mm AISI 304 stainless steel with RGB LED lights remote control & with installation kit for false ceiling <ul style="list-style-type: none"> Chromo therapy (RGB): LED x 0.23W with 12V Power Supply (SMPS) Including Controller, connecting to AC 100-240V, 50-60Hz 4-functions <ul style="list-style-type: none"> Rain, Intense, Waterfall, Water Column
Flow Rate	Rain - 51.20 LPM @ 3 bar Intense - 41.60 LPM @ 3 bar Waterfall - 48.20 LPM @ 3 bar Water Column - 23.30 LPM @ 3 bar
Recommended Water Pressure	1.0 Bar - 3.0 Bar
Mount Type	Ceiling Mounting
Spray Modes	Rain, Intense, Waterfall & Water Column Functions
Material Composition Specification in Percentage	STAINLESS STEEL: Nickel 8.0-11.0, Chromium 18.0-20.0, Manganese 0.0 - 2.0, Carbon 0.0-0.08, Iron Remainder (AISI 304) ABS: Specific Gravity (g/cm ³) 1.06-1.10, Melt Mass Flow Rate (g/10 min.) 20-26, Rockwell Hardness 95-115, DTUL @ 66 psi (0.45 MPa) (OC) 78-102
REMOTE CONTROL	 <p>ON/OFF</p> <p>Speed Down Push - button to speed down panoramic mode</p> <p>Mono color - next</p> <p>Mono color - previous</p> <p>Automatic mode changing - next</p> <p>Panoramic Mode ON</p> <p>Speed Up Push - button to speed up panoramic mode</p> <p>Increase Brightness of LED</p> <p>Decrease Brightness of LED</p> <p>Automatic mode changing previous</p> <p>HOW TO CHANGE BATTERY</p>
LED POWER SUPPLY	<ul style="list-style-type: none"> CHROMO THERAPY (RGB) LED x 0.23W with 12V Power Supply (SMPS) including Controller, connecting to AC 100-240V, 50-60Hz COLOR VARIATION <div style="display: flex; justify-content: space-around; align-items: center;"> <div style="text-align: center;"> <p>Mono Color (RGB)</p>  </div> <div style="text-align: center;"> <p>Chromo Therapy</p>  <p>LED On / Off Switch Sensor by Remote Control</p> </div> </div>
Finish	Salt Spray (500 hrs + Validated) Adhesion (Pass)
Available Finishing	Black Matt (BLM)
DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. 10% variation in flow rate may be possible. Jaquar reserves the right to make the necessary amendments at any time without prior notice.	