



|   |  |
|---|--|
| <b>Product Code (Only For CHR Finish)</b>   | <b>OSA-CHR-70001BR</b><br>False ceiling installation kit for RaiNJOY Shower 370X250mm consisting of 1 Bracket, 4 Anchors, 4 Stud bolts, 12 Hex nuts (Compatible with OSA-70001SH)  |
| <b>Product Code (Only For CHR Finish)</b>   | <b>OSA-CHR-70001SH</b><br>RaiNJOY Shower 370X250mm AISI 304 stainless steel without installation kit for false ceiling<br><ul style="list-style-type: none"> <li>• 2-functions                             <ul style="list-style-type: none"> <li>▪ Rain, ▪ 2 X Mist</li> </ul> </li> </ul>            |
| <b>Product Code (Only For Colour Finish)</b>  | <b>OSA-XXX-70001</b><br>RaiNJoy Shower 370X250mm AISI 304 stainless steel <b>with installation kit for false ceiling</b><br><ul style="list-style-type: none"> <li>• 2-functions                             <ul style="list-style-type: none"> <li>▪ Rain</li> <li>▪ 2 X Mist</li> </ul> </li> </ul>  |
| <b>Flow Rate</b>  | Rain - 17.72 LPM @ 3 bar<br>Mist - 01.03 LPM @ 3 bar   |
| <b>Recommended Water Pressure</b>   | 1.0 Bar - 3.0 Bar  |
| <b>Mount Type</b>   | Ceiling Mounting   |
| <b>Spray Modes</b>  | Rain & Mist Functions  |
| <b>Material Composition Specification in Percentage</b>   | <b>STAINLESS STEEL:</b> Nickel 8.0-11.0, Chromium 18.0-20.0, Manganese 0.0 - 2.0, Carbon 0.0-0.08, Iron Remainder (AISI 304)<br><br><b>ABS:</b> Specific Gravity (g/cm <sup>2</sup> ) 1.06-1.10, Melt Mass Flow Rate (g/10 min.) 20-26, Rockwell Hardness 95-115, DTUL @ 66 psi (0.45 MPa) (0C) 78-102 |
| <b>Finish</b>   | Salt Spray (600 hrs + Validated)<br>Adhesion (Pass)  |
| <b>Available Finishing</b>  | Antique Bronze (ABR), Antique Copper (ACR), Black Chrome (BCH), Blush Gold Bright PVD (BGP), Black Matt (BLM), Black Pearl PVD (BLP), Gold Bright PVD (GBP), Gold Matt PVD (GMP), Graphite (GRF) & Stainless Steel (SSF).  |
| DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. 10% variation in flow rate may be possible. Jaquar reserves the right to make the necessary amendments at any time without prior notice. |  |