



|  |   |
|--|---|
| <b>Product Code</b>                      | SPT-CHR-47463   |
| <b>Description</b>                       | Cellini Bath Tub Spout with Button Attachment for Hand Shower with Wall Flange  |
| <b>Flow Rate</b>                         | 38.88 LPM @ 3 bar   |
| <b>Recommended Water Pressure</b>        | 0.5 Bar - 5 Bar   |
| <b>Brass Specification in Percentage</b> | <p><b>Brass Ingots as per IS:1264-1997</b><br/>Cu (58.0-63.0), Sn (0.0-1.0), Pb (0.5-2.5), Ni (0.0-1.0), Al (0.2-0.8), Mn (0.0-0.5), Total Impurity (0.0-2.0), Zn (Remainder)</p> <p><b>Brass Rod as per IS:319-1989</b><br/>Cu (56.0-59.0), Pb (2.0-3.5), Fe (0.0-0.35), Total Impurity (0.0-0.7), Zn (Remainder)</p> <p><b>Brass Sheets as per IS:410-1977</b><br/>Cu (61.5-64.5), Pb (0.0-0.3), Fe (0.0-0.075), Total Impurity (0.0-0.6), Zn (Remainder)</p> |
| <b>Water Tightness</b>                   | 16 bar (Pass)   |
| <b>Pressure Resistance</b>               | 25 bar (Pass)   |
| <b>Finish</b>                            | Plating: Nickel-13.0 micron Chromium-0.40 micron<br>Salt Spray (600 hrs + Validated)<br>Adhesion (Pass)   |
| <b>Available Colour Finishing</b>        | CHROME (CHR)  |

DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. 10% variation in flow rate may be possible. Jaquar reserves the right to make the necessary amendments at any time without prior notice.