



|  |  |
|--|--|
| <b>Product Code</b>  | SPT-CHR-515429   |
| <b>Description</b>   | Navia Bath Spout With Wall Flange  |
| <b>Flow Rate</b>   | 31.99 LPM @ 3 bar  |
| <b>Recommended Water Pressure</b>  | 0.5 Bar - 5 Bar  |
| <b>Material Composition Specification in Percentage</b>  | <p><b>Brass Ingots as per IS:1264-1997</b><br/>Cu (58.0-63.0), Sn (0.0-1.0), Pb (0.5-2.5), Ni (0.0-1.0), Al (0.2-0.8), Mn (0.0-0.5), Total Impurity (0.0-2.0), Zn (Remainder)</p> <p><b>Brass Rod as per IS:319-1989</b><br/>Cu (56.0-59.0), Pb (2.0-3.5), Fe (0.0-0.35), Total Impurity (0.0-0.7), Zn (Remainder)</p> <p><b>S.S Sheets as per AISI : 304</b><br/>Ni (8.0-11.0), Ch (18.0-20.0), Mn (0.0-0.2), Ca (0.0-0.08), Fe (Remainder)</p> |
| <b>Water Tightness</b>   | 16 bar (Pass)  |
| <b>Pressure Resistance</b>   | 25 bar (Pass)  |
| <b>Finish</b>  | Plating: Nickel-13.0 micron Chromium-0.40 micron<br>Salt Spray (600 hrs + Validated)<br>Adhesion (Pass)  |
| <b>Aerator Size</b>  | M24X1  |
| <b>Available Colour Finishing</b>  | Black Matt (BLM), Blush Gold Bright PVD (BGP), Black Pearl PVD (BLP) & Gold Bright PVD (GBP)   |
| <p>DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. 10% variation in flow rate may be possible. Jaquar reserves the right to make the necessary amendments at any time without prior notice.</p> |  |