



Product Code	XQU-CHR-43051B
Description	Single Lever Basin Mixer with Pop-up Waste System & 450mm Long Braided Hoses
Connection Size	Braided hoses, 1/2" FIP (WRAS Approved) Withstand pressure of 10 Bar
Flow Rate	6.29 LPM @ 3 bar
Recommended Water Pressure	1.0 Bar - 5 Bar
Brass Specification in Percentage	<p>Brass Ingots as per IS:1264-1997 Cu (58.0-63.0), Sn (0.0-1.0), Pb (0.5-2.5), Ni (0.0-1.0), Al (0.2-0.8), Mn (0.0-0.5), Total Impurity (0.0-2.0), Zn (Remainder)</p> <p>Brass Rod as per IS:319-1989 Cu (56.0-59.0), Pb (2.0-3.5), Fe (0.0-0.35), Total Impurity (0.0-0.7), Zn (Remainder)</p> <p>Brass Sheets as per IS:410-1977 Cu (61.5-64.5), Pb (0.0-0.3), Fe (0.0-0.075), Total Impurity (0.0-0.6), Zn (Remainder)</p>
Cartridge Specification	<p>Cartridge with Brass Spindle</p> <p>Life Cycle EN 817: 70,000 cycles (Standard)</p> <ul style="list-style-type: none"> - 2.1 LAC Cycles as per EN 817* - 10.5 LAC Cycles (ON/OFF)*
Accessories incl.	Pop-up waste 1¼"
Water Tightness	16 bar (Pass)
Pressure Resistance	25 bar (Pass)
Finish	<p>Plating: Nickel-13.0 micron Chromium-0.40 micron</p> <p>Salt Spray (600 hrs + Validated)</p> <p>Adhesion (Pass)</p>
Available Colour Finishing	CHROME (CHR)
* As per in-house testing done on automatic life cycle testing machine made by Giussain, Italy	
DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. 10% variation in flow rate may be possible. Jaquar reserves the right to make the necessary amendments at any time without prior notice.	