					SGS-WHT	-41805
Artize						
			SPECIFICATION	DATA SHEET		
			PRODUCT	DETAILS		
Manufacturer :	Artize			Type:	Wall Hung Basin	
Range	Signac			Colour:	White	
Outlet	Horizontal			Material:	Ceramic - Vitreous	China
		tap hole 35Ø +2 -1		BOM doc.N0.	ASW/03/2018/05	
Technical Details:		et hole 45 Ø+2 -3 m				
	Horizontal distan		ntre line of the tap ho ARTICLE NAME: WAL		e of the waste outlet	hole ≤ 165 mm
			TECHNICAL DI 1000- 1000- 1000- 1000- 100- 100- 100-			
		FL.LVI				
Length (mm) 1000		T DIMENSIONS Height (mm) 160	BACK VIEW Net weight (kg) 23.15		SIDE VI	
Length (mm)	PRODUC Width (mm) 520	Height (mm) 160	BACK VIEW		USP h over flow hole cap	ALL DIMENSIONS ARE IN MM. (TOLERANCE ± 5 MM)
Length (mm)	PRODUC Width (mm) 520 Overflow	Height (mm) 160 hole Cap	BACK VIEW Net weight (kg) 23.15		USP h over flow hole cap ZPS-WHT	ALL DIMENSIONS ARE IN MM. (TOLERANCE ± 5 MM)
Length (mm) 1000	PRODUC Width (mm) 520 Overflow Rag	Height (mm) 160 7 hole Cap 5 bolt	BACK VIEW Net weight (kg) 23.15 ACCESSORIES CARE AND CLEANI	PROVIDED	USP h over flow hole cap ZPS-WHT ZPS-SNS-	ALL DIMENSIONS ARE IN MM. (TOLERANCE ± 5 MM) and anti germ glaze
Length (mm) 1000 Vitreous china sani handling, installation : The product is heav Carefully inspect th Risk of product dar Risk of external lea Always test your cl Do not allow cleand Use a soft, damper Wipe surfaces clean Clean Chrome, stai immediately to preve	PRODUC Width (mm) 520 Overflow Rag tary ware products and use thereafter y and it is recomn e new product for nage. Over tighten kage. Do not lift or eaning solution on ers to sit or soak or lead sponge or clott n and rinse comple nless steel surfaces nt corrosion.	Height (mm) 160 hole Cap bolt s are fragile in natu nended that two per damage before ins ing may cause breat r rock the bowl after an inconspicuous a n the product. to clean. Never us etely with water imits s once a week. Do r	BACK VIEW Net weight (kg) 23.15 ACCESSORIES CARE AND CLEANII re and need to be han ersons hold it while it is stallation. akage or chipping of vir er placement. area on the product be area on the product be the abrasive material lik mediately after applyin not use cleaners conta	PROVIDED NG GUIDELINES dled with care (to a s being fixed. treous china. efore applying it to t er a bristle brush or ng cleaners. ining chloride on ch an and then dry witi	USP h over flow hole cap ZPS-WHT ZPS-SNS- void personal injury) a he entire surface. scouring pad. rome, stainless steel. I	ALL DIMENSIONS ARE IN MM. (TOLERANCE ± 5 MM)
Length (mm) 1000 Vitreous china sani handling, installation : The product is heav Carefully inspect th Risk of product dar Risk of external lea Always test your cl Do not allow cleand Use a soft, damper Wipe surfaces clean Clean Chrome, stai immediately to preve	PRODUC Width (mm) 520 Overflow Rag tary ware products and use thereafter y and it is recomn e new product for nage. Over tighten kage. Do not lift or eaning solution on ers to sit or soak or lead sponge or clott n and rinse comple nless steel surfaces nt corrosion. plating is used on t	Height (mm) 160 hole Cap bolt s are fragile in natu nended that two per damage before ins ing may cause breat r rock the bowl after an inconspicuous a n the product. to clean. Never us etely with water imits s once a week. Do r	BACK VIEW Net weight (kg) 23.15 ACCESSORIES CARE AND CLEANII re and need to be han ersons hold it while it is itallation. akage or chipping of vir r placement. area on the product be se abrasive material lik mediately after applyin hot use cleaners conta	PROVIDED NG GUIDELINES dled with care (to a s being fixed. treous china. efore applying it to t er a bristle brush or ng cleaners. ining chloride on ch an and then dry witi	USP h over flow hole cap ZPS-WHT ZPS-SNS- void personal injury) a he entire surface. scouring pad. rome, stainless steel. I	ALL DIMENSIONS ARE IN MM. (TOLERANCE ± 5 MM) and anti germ glaze -9014 RB08 t all times during its storage,
Length (mm) 1000 * Vitreous china sani handling, installation * The product is heav * Carefully inspect th * Risk of product dar * Risk of external lea * Always test your cl * Do not allow cleand * Use a soft, damper * Wipe surfaces cleand * Clean Chrome, stai immediately to prevend * Wherever chrome	PRODUC Width (mm) 520 Overflow Rag tary ware products and use thereafter y and it is recomn e new product for nage. Over tighten kage. Do not lift or eaning solution on ers to sit or soak or lead sponge or clott n and rinse comple nless steel surfaces nt corrosion. plating is used on t	Height (mm) 160 160 160 160 160 160 160 160	BACK VIEW Net weight (kg) 23.15 ACCESSORIES CARE AND CLEANII re and need to be han ersons hold it while it is stallation. akage or chipping of vir er placement. area on the product be area on the product be the abrasive material lik mediately after applyin not use cleaners conta	PROVIDED NG GUIDELINES dled with care (to a s being fixed. treous china. efore applying it to t er a bristle brush or ng cleaners. ining chloride on ch an and then dry witi	USP h over flow hole cap ZPS-WHT ZPS-SNS- void personal injury) a he entire surface. scouring pad. rome, stainless steel. I	ALL DIMENSIONS ARE IN MM. (TOLERANCE ± 5 MM) and anti germ glaze -9014 RB08 t all times during its storage,
Length (mm) 1000 Vitreous china sani handling, installation : The product is heav Carefully inspect th Risk of product dar Risk of product dar Always test your cl Do not allow cleand Use a soft, damper Wipe surfaces cleand Clean Chrome, stai immediately to preve Wherever chrome Compliance : :MS 15	PRODUC Width (mm) 520 Overflow Rag tary ware products and use thereafter y and it is recomm e new product for nage. Over tighten kage. Do not lift or eaning solution on ers to sit or soak on ted sponge or cloth n and rinse compleaners to corrosion. plating is used on t 22:2015	Height (mm) 160 160 160 160 160 160 160 160	BACK VIEW Net weight (kg) 23.15 ACCESSORIES CARE AND CLEANII re and need to be han ersons hold it while it is itallation. akage or chipping of vir r placement. area on the product be the abrasive material lik mediately after applyin not use cleaners conta nly warm water to clean CERTIFIC	PROVIDED NG GUIDELINES dled with care (to a s being fixed. treous china. fore applying it to t te a bristle brush or ng cleaners. ining chloride on ch an and then dry with ATION	USP h over flow hole cap ZPS-WHT ZPS-SNS- void personal injury) a he entire surface. scouring pad. rome, stainless steel. I n a soft cloth.	ALL DIMENSIONS ARE IN MM. (TOLERANCE ± 5 MM) To and anti germ glaze -9014 RB08 t all times during its storage, If used, rinse the surface
Length (mm) 1000 Vitreous china sani handling, installation a The product is heav Carefully inspect th Risk of product dar Risk of external lea Always test your cl Do not allow cleand Use a soft, damper Wipe surfaces cleand Clean Chrome, stai immediately to prevent Wherever chrome	PRODUC Width (mm) 520 Overflow Rag tary ware products and use thereafter y and it is recomm e new product for nage. Over tighten kage. Do not lift or eaning solution on ers to sit or soak or ied sponge or cloth n and rinse comple nless steel surfaces th corrosion. plating is used on t 22:2015 PACKAGI	Height (mm) 160 160 160 160 160 160 160 160	BACK VIEW Net weight (kg) 23.15 ACCESSORIES CARE AND CLEANII re and need to be han ersons hold it while it is itallation. ikage or chipping of vii rr placement. area on the product be se abrasive material lik mediately after applyii not use cleaners conta nly warm water to clea CERTIFIC Gross Weight(kg)	PROVIDED NG GUIDELINES dled with care (to a s being fixed. treous china. fore applying it to t te a bristle brush or ng cleaners. ining chloride on ch an and then dry with ATION Length (mm)	USP h over flow hole cap ZPS-WHT ZPS-SNS- void personal injury) a he entire surface. scouring pad. rome, stainless steel. I n a soft cloth.	ALL DIMENSIONS ARE IN MM. (TOLERANCE ± 5 MM) a and anti germ glaze -9014 RB08 t all times during its storage, If used, rinse the surface LET DETAIL Height (mm] no of pieces on pallet
Length (mm) 1000 Vitreous china sani handling, installation : The product is heav Carefully inspect th Risk of product dar Risk of product dar Always test your cl Do not allow cleand Use a soft, damper Wipe surfaces cleand Clean Chrome, stai immediately to preve Wherever chrome Compliance : :MS 15	PRODUC Width (mm) 520 Overflow Rag tary ware products and use thereafter y and it is recomm e new product for nage. Over tighten kage. Do not lift or eaning solution on ers to sit or soak on ted sponge or cloth n and rinse compleaners to corrosion. plating is used on t 22:2015	Height (mm) 160 160 160 160 160 160 160 160	BACK VIEW Net weight (kg) 23.15 ACCESSORIES CARE AND CLEANII re and need to be han ersons hold it while it is itallation. akage or chipping of vir r placement. area on the product be the abrasive material lik mediately after applyin not use cleaners conta nly warm water to clean CERTIFIC	PROVIDED NG GUIDELINES dled with care (to a s being fixed. treous china. fore applying it to t te a bristle brush or ng cleaners. ining chloride on ch an and then dry with ATION	USP h over flow hole cap ZPS-WHT ZPS-SNS- void personal injury) a he entire surface. scouring pad. rome, stainless steel. I n a soft cloth.	ALL DIMENSIONS ARE IN MM. (TOLERANCE ± 5 MM) To and anti germ glaze -9014 RB08 t all times during its storage, If used, rinse the surface